

## Isolation Tapes



MODEL	LENGTH mt	WIDTH mm	SPECIFICATIONS
DECORATIVE STRIP	25	50	Cream colour decorative strip
BLACK PVC STRIP	25	50	Black colour PVC strip
STRIP WITH PITCH	10	50	Strip with pitch (self stick)

### Closed Pore Rubber Foam

It's a completely flexible insulation product with elastomeric closed cell. It provides high productivity in heat gains and efficient against the heat loss. It's used in heating and cooling systems, covering the large diameter pipes, fittings, chiller units, insulation of the tanks and air ducts.

Thickness : 6-9-13-19-25-32-50 mm

Width : From 10 mm to 980 mm

Special sized forms according to customer request.



TECHNICAL PROPERTIES	TEST METHOD	VALUE
Cellular Structure	Closed	
Temperature Range ( °C )	DIN 53515	-100 / 105
Thermal Conductivity ( W/Mk )	DIN 52612/52613 0°C	λ 0,034
Water Vapour Permeability	DIN 52615 BS 4370/2	7000 μ 0,09 μgm/Nh
Fire Rating	UNI 8457 - UNI 9174 BS 476: Part7 BS 476: part6	Class 1 Class 1 Class 0
Density ( kg/m3 )	ISO 845 - 88	45 - 65
Noise Reduction	EN 20140-10	35dB / 500Hz
Closed Cell Content ( % )	> 90	
Water Resistance ( % )	Good	
Odour	Neutral	
Color	Black	
Ozone Resistance	ASTM D 1171	NO CROCKING
Oil Resistance	Excellent	

## Isolation Tapes



MODEL	LENGTH mt	WIDTH mm	SPECIFICATIONS
DECORATIVE STRIP	25	50	Cream colour decorative strip
BLACK PVC STRIP	25	50	Black colour PVC strip
STRIP WITH PITCH	10	50	Strip with pitch (self stick)

### Closed Pore Rubber Foam

It's a completely flexible insulation product with elastomeric closed cell. It provides high productivity in heat gains and efficient against the heat loss. It's used in heating and cooling systems, covering the large diameter pipes, fittings, chiller units, insulation of the tanks and air ducts.

Thickness : 6-9-13-19-25-32-50 mm

Width : From 10 mm to 980 mm

Special sized forms according to customer request.

TECHNICAL PROPERTIES	TEST METHOD	VALUE
Cellular Structure	Closed	
Temperature Range ( °C )	DIN 53515	-100 / 105
Thermal Conductivity ( W/Mk )	DIN 52612/52613	$\lambda$ 0,034
	0°C	
Water Vapour Permeability	DIN 52615	7000 $\mu$
	BS 4370/2	0,09 $\mu$ gm/Nh
Fire Rating	UNI 8457 - UNI 9174	Class 1
	BS 476: Part7	Class 1
	BS 476: part6	Class 0
Density ( kg/m3 )	ISO 845 - 88	45 - 65
Noise Reduction	EN 20140-10	35dB / 500Hz
Closed Cell Content ( % )	> 90	
Water Resistance ( % )	Good	
Odour	Neutral	
Color	Black	
Ozone Resistance	ASTM D 1171	NO CROCKING
Oil Resistance	Excellent	

